

[Re-Select](#)

E100
Notebook/Tablet

[Remove](#)

Operating System

Genuine Windows® XP Tablet Edition
Genuine Windows Vista® Compatible

Mobile Computing Platform

Intel® A110 800MHz
- 400 MHz FSB
- 512KB L2 cache
- Mobile Intel® 945GU Chipset

VGA Controller

Intel® Graphics Media Accelerator GMA950
Max. 144MB shared memory

Display

8.4" TFT LCD SVGA (800 x 600)
Optional 800 nits QuadraClear™ sunlight readable display with touchscreen

Storage & Memory

512MB DDR2 expandable to 1GB
PATA HDD 80GB
Optional PATA SSD 32GB

Keyboard

LED backlit numeric keypad

Pointing Device

Touchscreen
- Pressure sensitive touchscreen

Expansion Slots

PCMCIA Type II x 1

Multimedia Bay

IO Interface

Optional 2MB pixels camera
Audio output (Mini-jack) x 1
DC in Jack x 1
USB 2.0 (4-pin) x 2
LAN (RJ45) x 1
Docking connector x 1
RF antenna pass-through for GPS and WWAN



P470
Notebook/Tablet

[Remove](#)

Genuine Windows® XP Professional
Genuine Windows® Vista Business

Intel® Centrino® Technology
- Intel® Core™2 Duo Processor T7200 2.0GHz
- 667 MHz FSB
- 4MB L2 cache
- Mobile Intel® 945GM chipset

Intel® Graphics Media Accelerator 950,
Max. 128MB shared memory

14.1" TFT LCD WXGA (1280 x 800)
Standard display with protection glass
Optional 500 nits QuadraClear™ sunlight readable display
Optional touchscreen

"1GB DDR2 expandable to 4GB
SATA HDD 160GB"

Membrane keyboard
Optional project keyboard lighting

Touchscreen
- Optional pressure sensitive touchscreen
Touchpad
- Glide touchpad with scroll bar

PCMCIA Type II x 1
ExpressCard 34/54mm
Multi memory card reader x 1

DVD super multi drive
Optional 2nd battery
Optional 2nd HDD 160GB

Optional 1.3MB pixels webcam
Serial port (9-pin; D-sub) x 1
External VGA (15-pin; D-sub) x 1
Audio output (Mini-jack) x 1
Microphone (Mini-jack) x 1
DC in Jack x 1
USB 2.0 (4-pin) x 3
Modem (RJ11) x 1



V100
Notebook/Tablet

[Remove](#)

Genuine Windows Vista® Business
Genuine Windows® XP Tablet Edition
Genuine Windows® 7 Professional

Intel® Centrino® Technology
- Intel® Core™2 Duo Processor SU9400 1.4GHz
- 800 MHz FSB
- 3MB L2 cache
- Intel® GS45 Chipset

Intel® Graphics Media Accelerator X4500HD
Max. 384MB shared memory

10.4" TFT LCD XGA (1024 x 768)
Optional 1200 nits QuadraClear™ sunlight readable display with touchscreen
Optional digitizer mode

1GB DDR2 expandable to 4GB
SATA HDD 160GB/320GB
4GB Turbo Memory

Membrane keyboard
Optional LED backlit rubber keyboard

Touchscreen
- Pressure sensitive touchscreen
- Optional multi-touch touchscreen (glove type)
- Optional dual mode touchscreen (pressure sensitive touchscreen and digitizer)

Digitizer
- Optional digitizer

Touchpad
- Glide touchpad with scroll bar
- Optional resistive (Glove) touchpad

PCMCIA Type II x 1
Optional ExpressCard 34/54mm (occupies one smart card reader slot)
SD card reader x 1

Optional 1.3M pixels webcam
Serial port (9-pin; D-sub) x 1
External VGA (15-pin; D-sub) x 1
Microphone (Mini-jack) x 1
Audio output (Mini-jack) x 1
DC in Jack x 1
USB 2.0 (4-pin) x 2
Modem (RJ11) x 1

	LAN (RJ45) x 1 IEEE 1394a x 1 External GPS antenna port (only with optional GPS) x 1 Docking connector x 1	LAN (RJ45) x 1 Docking connector x 1
Communication Interface		
10/100/1000 base-T Ethernet WLAN 802.11 b/g Bluetooth (v2.1+EDR class 2) Optional GPS Optional EV-DO / GSM / GPRS / EDGE / UMTS / HSDPA Software	10/100/1000 base-T Ethernet 56K ITU V.92 modem Intel® PRO/Wireless 3945ABG Network Connection; 802.11 a/b/g Bluetooth (v2.0+EDR class 2) Optional GPS	10/100/1000 base-T Ethernet 56K ITU V.92 modem Intel® WiFi Link 5300; 802.11 a/b/g/Draft N Bluetooth (v2.0+EDR class 2) Optional GSM / GPRS / EDGE / UMTS / HSDPA Optional GPS
Getac Utility Getac Camera Computrace® Compatible BIOS Adobe® Reader® Security Feature	Getac Utility Adobe® Reader®	Getac Utility Getac Camera Adobe® Reader® Computrace® Compatible BIOS
TPM 1.2 Kensington Lock Smart card reader	TPM 1.2 Fingerprint scanner Kensington lock Smart card reader	TPM 1.2 Smart Card Reader Kensington Lock
Power		
AC adapter (50W, 100-240V, 50/60Hz) Li-Ion smart battery (5100mAh) (up to 5 hours of battery life)**	AC adapter (90W, 100-240V, 50 / 60Hz) Li-Ion smart battery (4800mAh) Optional Li-Ion smart battery (7200mAh) Optional Media Bay 2nd Li-Ion smart battery (3800mAh)	AC Adapter (60W, 100-240V, 50/60 Hz) Optional AC Adapter(90W, 100-240V, 50/60 Hz) Li-Ion smart battery (5200mAh) Optional Li-Ion smart battery (7800mAh)
Dimensions (W x H x D) & Weight		
280 x 184 x 32 mm (11.02" x 7.2" x 1.26"), 1.4kg (3 lbs)	333 x 254~295 x 42 mm (13.1" x 10"~11.6" x 1.65") 2.95kg (6.4 lbs)	289.68 x 222 x 49mm (11.4"x 8.74" x 1.93"), 2.3 Kgs (5.07 lbs)
Rugged Features		
Fully rugged MIL-STD-810G certified and IP65 compliance Optional UL1604 Class 1, Division 2, Group A, B, C, D Full magnesium alloy case Shock-protected HDD Vibration & drop resistant	MIL-STD-810F vibration, shock, Thermal shock and altitude compliance Magnesium alloy case Sealed ports and connectors Shock-protected removable HDD Wide range temperature and humidity Drop resistant	Fully rugged MIL-STD 810G and IP65 compliance Optional MIL-STD 461F certified EU Explosive Atmosphere ATEX certified Optional UL1604 Class 1, Division 2, Group A, B, C, D Full magnesium alloy case Shock-protected removable HDD Vibration & drop resistant
Environmental Specification		
Temperature: - Operating: 0°C to 60°C / 32°F to 140°F Optional low temperature: -20°C / -4°F - Storage: -40°C to 71°C / -40°F to 160°F Humidity: -95% RH , non-condensing	Temperature: - Operating: 0°C to 45°C / -32°F to 113°F - Storage: -40°C to 70°C / -40°C to 158°F Humidity: - 95% RH, non-condensing	Temperature: - Operating: 0°C to 55°C / 32°F to 131°F (Optional low temperature: -20°C / -4°F) - Storage: -40°C to 71°C / -40°F to 160°F Humidity: - 95% RH, non-condensing