

[Re-Select](#)

E100
Notebook/Tablet

[Remove](#)

Operating System

Genuine Windows® XP Tablet Edition
Genuine Windows Vista® Compatible

Mobile Computing Platform

Intel® A110 800MHz
- 400 MHz FSB
- 512KB L2 cache
- Mobile Intel® 945GU Chipset

VGA Controller

Intel® Graphics Media Accelerator GMA950
Max. 144MB shared memory

Display

8.4" TFT LCD SVGA (800 x 600)
Optional 800 nits QuadraClear™ sunlight readable display with touchscreen

Storage & Memory

512MB DDR2 expandable to 1GB
PATA HDD 80GB
Optional PATA SSD 32GB

Keyboard

LED backlit numeric keypad

Pointing Device

Touchscreen
- Pressure sensitive touchscreen

Expansion Slots

PCMCIA Type II x 1

Multimedia Bay

IO Interface

Optional 2MB pixels camera
Audio output (Mini-jack) x 1
DC in Jack x 1
USB 2.0 (4-pin) x 2
LAN (RJ45) x 1
Docking connector x 1
RF antenna pass-through for GPS and WWAN



P470
Notebook/Tablet

[Remove](#)

Genuine Windows® XP Professional
Genuine Windows® Vista Business

Intel® Centrino® Technology
- Intel® Core™2 Duo Processor T7200 2.0GHz
- 667 MHz FSB
- 4MB L2 cache
- Mobile Intel® 945GM chipset

Intel® Graphics Media Accelerator 950,
Max. 128MB shared memory

14.1" TFT LCD WXGA (1280 x 800)
Standard display with protection glass
Optional 500 nits QuadraClear™ sunlight readable display
Optional touchscreen

"1GB DDR2 expandable to 4GB
SATA HDD 160GB"

Membrane keyboard
Optional project keyboard lighting

Touchscreen
- Optional pressure sensitive touchscreen
Touchpad
- Glide touchpad with scroll bar

PCMCIA Type II x 1
ExpressCard 34/54mm
Multi memory card reader x 1

DVD super multi drive
Optional 2nd battery
Optional 2nd HDD 160GB

Optional 1.3MB pixels webcam
Serial port (9-pin; D-sub) x 1
External VGA (15-pin; D-sub) x 1
Audio output (Mini-jack) x 1
Microphone (Mini-jack) x 1
DC in Jack x 1
USB 2.0 (4-pin) x 3
Modem (RJ11) x 1



V100
Notebook/Tablet

[Remove](#)

Genuine Windows Vista® Business
Genuine Windows® XP Tablet Edition
Genuine Windows® 7 Professional

Intel® Centrino® Technology
- Intel® Core™2 Duo Processor SU9400 1.4GHz
- 800 MHz FSB
- 3MB L2 cache
- Intel® GS45 Chipset

Intel® Graphics Media Accelerator X4500HD
Max. 384MB shared memory

10.4" TFT LCD XGA (1024 x 768)
Optional 1200 nits QuadraClear™ sunlight readable display with touchscreen
Optional digitizer mode

1GB DDR2 expandable to 4GB
SATA HDD 160GB/320GB
4GB Turbo Memory

Membrane keyboard
Optional LED backlit rubber keyboard

Touchscreen
- Pressure sensitive touchscreen
- Optional multi-touch touchscreen (glove type)
- Optional dual mode touchscreen (pressure sensitive touchscreen and digitizer)

Digitizer
- Optional digitizer

Touchpad
- Glide touchpad with scroll bar
- Optional resistive (Glove) touchpad

PCMCIA Type II x 1
Optional ExpressCard 34/54mm (occupies one smart card reader slot)
SD card reader x 1

Optional 1.3M pixels webcam
Serial port (9-pin; D-sub) x 1
External VGA (15-pin; D-sub) x 1
Microphone (Mini-jack) x 1
Audio output (Mini-jack) x 1
DC in Jack x 1
USB 2.0 (4-pin) x 2
Modem (RJ11) x 1

	LAN (RJ45) x 1 IEEE 1394a x 1 External GPS antenna port (only with optional GPS) x 1 Docking connector x 1	LAN (RJ45) x 1 Docking connector x 1
Communication Interface		
10/100/1000 base-T Ethernet WLAN 802.11 b/g Bluetooth (v2.1+EDR class 2) Optional GPS Optional EV-DO / GSM / GPRS / EDGE / UMTS / HSDPA	10/100/1000 base-T Ethernet 56K ITU V.92 modem Intel® PRO/Wireless 3945ABG Network Connection; 802.11 a/b/g Bluetooth (v2.0+EDR class 2) Optional GPS	10/100/1000 base-T Ethernet 56K ITU V.92 modem Intel® WiFi Link 5300; 802.11 a/b/g/Draft N Bluetooth (v2.0+EDR class 2) Optional GSM / GPRS / EDGE / UMTS / HSDPA Optional GPS
Software		
Getac Utility Getac Camera Computrace® Compatible BIOS Adobe® Reader®	Getac Utility Adobe® Reader®	Getac Utility Getac Camera Adobe® Reader® Computrace® Compatible BIOS
Security Feature		
TPM 1.2 Kensington Lock Smart card reader	TPM 1.2 Fingerprint scanner Kensington lock Smart card reader	TPM 1.2 Smart Card Reader Kensington Lock
Power		
AC adapter (50W, 100-240V, 50/60Hz) Li-Ion smart battery (5100mAh) (up to 5 hours of battery life)**	AC adapter (90W, 100-240V, 50 / 60Hz) Li-Ion smart battery (4800mAh) Optional Li-Ion smart battery (7200mAh) Optional Media Bay 2nd Li-Ion smart battery (3800mAh)	AC Adapter (60W, 100-240V, 50/60 Hz) Optional AC Adapter(90W, 100-240V, 50/60 Hz) Li-Ion smart battery (5200mAh) Optional Li-Ion smart battery (7800mAh)
Dimensions (W x H x D) & Weight		
280 x 184 x 32 mm (11.02" x 7.2" x 1.26"), 1.4kg (3 lbs)	333 x 254~295 x 42 mm (13.1" x 10"~11.6" x 1.65") 2.95kg (6.4 lbs)	289.68 x 222 x 49mm (11.4"x 8.74" x 1.93"), 2.3 Kgs (5.07 lbs)
Rugged Features		
Fully rugged MIL-STD-810G certified and IP65 compliance Optional UL1604 Class 1, Division 2, Group A, B, C, D Full magnesium alloy case Shock-protected HDD Vibration & drop resistant	MIL-STD-810F vibration, shock, Thermal shock and altitude compliance Magnesium alloy case Sealed ports and connectors Shock-protected removable HDD Wide range temperature and humidity Drop resistant	Fully rugged MIL-STD 810G and IP65 compliance Optional MIL-STD 461F certified EU Explosive Atmosphere ATEX certified Optional UL1604 Class 1, Division 2, Group A, B, C, D Full magnesium alloy case Shock-protected removable HDD Vibration & drop resistant
Environmental Specification		
Temperature: - Operating: 0°C to 60°C / 32°F to 140°F Optional low temperature: -20°C / -4°F - Storage: -40°C to 71°C / -40°F to 160°F Humidity: -95% RH , non-condensing	Temperature: - Operating: 0°C to 45°C / -32°F to 113°F - Storage: -40°C to 70°C / -40°C to 158°F Humidity: - 95% RH, non-condensing	Temperature: - Operating: 0°C to 55°C / 32°F to 131°F (Optional low temperature: -20°C / -4°F) - Storage: -40°C to 71°C / -40°F to 160°F Humidity: - 95% RH, non-condensing